



## RFO-HTCR1515

**UHF High Temperature Tag**  
**225°C**

Functional Specifications:		RFO-HTCR138
RFID Protocol		UHF EPC Class 1 Gen 2, ISO 18000-6C, ISO 17364, DIN 40050-9
Frequency		US 902-928MHz, EU 865-868MHz
IC type		Higgs 3
Memory		96 bit EPC, 512 bit UM
Anti-Collision		Yes
Reading Distance (2W reader ERP, free space)		32.8 ft (10m)
Physical Specification:		
Size		0.6 x 0.6 x 0.22 in (15.3 x 15.3 x 5.6 mm)
Material		Ceramic painted
Colour		Black
Weight		0.18 oz (5 g)
Mounting Methods		Adhesive or enclosure
Affixes To		Metal surfaces
CHEMICAL, MECHANICAL & THERMAL		
Water		IP68, 68° F (20° C), 1 m x 24 h
Withstands Exposure To		5% caustic soda, 10% salt water, vegetable oil, Motor oil 68° F (20° C), 168hr
Vibration & Shock		MIL STD 810-G
Warranty		1 year
Storage		-40° to +185° F (-40° to +85° C)
Operating Temperature		-40° to +185° F (-40° to +85° C)
Peak Temperature		437° F (225° C), 700 h
Shock/Fatigue		-40° to +185° F (-40° to +85° C), 100 x 5 min with 30 sec transition
OTHER		
Options		Self-adhesive sticker (for placement only in applications exceeding +85°C), ATEX/IECEx, C1D1
Box Size		500 pcs.